



TECHNICAL DATA

Rubex MS

HIGH PERFORMANCE ELASTOMERIC ADHESIVE/SEALANT

PRODUCT DESCRIPTION:

Rubex MS exhibits excellent adhesion to many substrates including aluminum, brass, steel, glass, granite, marble, wood and many plastics. Cures fast, even at low temperatures. Rubex MS is highly weather resistant and can be painted with most paints. Contains no solvents or isocyanates and is non-yellowing. USDA accepted. Conforms to ASTM C920, Type S, Grade NS, Class 25 and to AAMA 802.3 Type II Back Bedding Compound.

2. TECHNICAL DATA:

Tack Free Time	Less than an hour @ 77°F/50% RH
Skin Time	Less than 30 minutes @ 77°F/50% RH
Sag	Non-sagging
Tensile Strength	225 psi
Lap Shear (shear rate = 1" min)	275 psi
Elongation	275%
High Temperature Resistance	Up to 400°F for short periods
Low Temperature Flexibility	Properties retained to -75°F
Hardness	45-50
UV Ratings	After 2000 hours UV-A no change in appearance or physical properties (ASTM G26)
Corrosive Properties	Non-corrosive
Staining	Non-staining

3. COLORS:

White, colonial white, aluminum gray, black. Other colors available upon request.

4. PACKAGING:

10.3 ll. oz. cartridges, 10.3 & 20 fl. oz. sausage packs, 1, 3, 5, & 55 gallon containers.

5. SURFACE PREPARATION:

Apply to clean, dry surfaces free of contaminants that can adversely affect adhesion. Remove all old sealant before applying Rubex MS.

6. PAINTING:

Cured Rubex MS may be painted with most industrial & consumer paints. Testing prior to painting is recommended.

7. STORAGE LIFE:

Nine months. For maximum shelf life, store unopened product at or below 80°F.

8. PRECAUTIONS:

Use with adequate ventilation. Inhalation of vapor during application and cure may cause slight eye or throat irritation. In case of contact with eyes, lips, or mouth, flush thoroughly with water. If irritation persists, consult a physician. Avoid repeated, prolonged contact with skin. See MSDS for additional information. Keep out of reach of children.

9. TECHNICAL SERVICE:

Rubex technical representatives are always available to provide assistance. Please contact our Technical Service Department with your questions or requests for specific applications.

10. LIMITED WARRANTY:

Any goods proved defective will be replaced or the purchase price refunded. The limited warranty described herein is in lieu of any other warranty, expressed or implied, including any implied warranty of merchantability or fitness for a particular use. The user shall determine suitability of the product for its intended use. Liability for any incidental or consequential damage or loss is excluded. The user assumes all risks of the product's use, handling and storage.

Distributed by

RUBEX, INC.	tel	614 875 6343
3709 GROVE CITY ROAD	fax	614 875 9041
GROVE CITY, OHIO 43123	web	www.rubex-us.com